

											特殊仕様			
型式	標準 使用範囲	小径用使用範囲	標準取付け形式	適合 ハンドル	ハンドル 穴径	D	L ₁	L ₂	ツメリード	重量 (g) 本体	標準以外のテーパ	ステンレス製		
3mm	0.4～3.2	0.1、0.2	JT0	K-03	3.2	21	34	28.5	10	44				
4mm	0.4～4	0.1、0.2										SUS4		
D4mm	0.4～4	0.1、0.2	JTD	K-00	4	25	40	32.5	11	78				
D5mm	0.4～5	0.1、0.2								73				
5mmMG	0.5～5	0.2	JT1	K-01	4	31	48.5	40.5	12	138	JT0			
6.5mmEL	0.5～6.5									136		SUS6.5		
6.5ELネジ	0.5～6.5		⅜-24UNF							SUS6.5ネジ				
6.5mmMG	0.5～6.5		JT1	K-1A	5.5	35.5	54	45	13	200	JT0			
J8mm	0.5～8									200		SUSJ8		
J8mmネジ	0.5～8									⅜-24UNF	SUSJ8ネジ			
10mmEL	0.5～10		JT2S (角度は2と同じ)	K-1A	5.5	35.5	65	55	13	300	JT1,JTD			
10mmMG	0.5～10	0.3		K-2	6.5	43.8	68	55.5	19	355		SUS10		
10MGネジ	0.5～10		½-20UNF											
13mmEL	0.7～13		JT6 (JT2 ½と同じ)	K-2	6.5	44.5	80	63.5	19	500	JT2S,JT1			
13mmMG	0.7～13	0.3		K-13	8	55	88.5	68.5	26	700	JT33,B16 JT2S,JT1	SUS13		
13MGネジ	0.7～13										1/2-20UNF			SUS13ネジ
		5/8-16UNF												
14mm	0.7～14		JT3	K-14	9	59.5	96	73.5	26	915	JT6,JT2SS JT33			
16mm	3.2～16								31	910				
19mm	0.8～19		JT4	K-4	9.5	74	126	96.5	31.5	1830	JT3,JT6 JT33			
22mm	5～22								36	1800				
25mm	6～25.4		JT5	K-5	10.9	88	149	110.5	44	2880	JT4,JT6			