

型式	標準 使用範囲	小径用使用範囲	標準取付け形式	適合 ハンドル	ハンドル 穴径	D	L <sub>1</sub>	L <sub>2</sub>	ツメリード	重量(g) 本体	特殊仕様		
											標準以外のテーパ	ステンレス製	
3mm	0.4~3.2	0.1、0.2	JT0	K-03	3.2	21	34	28.5	10	44		SUS4	
4mm	0.4~4	0.1、0.2											
D4mm	0.4~4	0.1、0.2	JTD	K-00	4	25	40	32.5	11	78			
D5mm	0.4~5	0.1、0.2											
5mmMG	0.5~5	0.2	JT1	K-01	4	31	48.5	40.5	12	138	JT0	SUS6.5	
6.5mmEL	0.5~6.5									136			
6.5ELネジ	0.5~6.5		%-%24UNF	JT1	K-1A	5.5	35.5	54	45	13	200	JT0	SUS6.5ネジ
6.5mmMG	0.5~6.5												
J8mm	0.5~8		%-%24UNF	K-1A	5.5	35.5	65	55	13	300	JT1,JTD	SUS10	
J8mmネジ	0.5~8												
10mmEL	0.5~10		JT2S (角度は2と同じ)	K-1A	5.5	35.5	68	55.5	19	355	JT1,JTD	SUS13	
10mmMG	0.5~10	0.3											
10MGネジ	0.5~10		1/2-20UNF	K-2	6.5	43.8	68	55.5	19	355	JT33,B16 JT2S,JT1	SUS13ネジ	
13mmEL	0.7~13		JT6 (JT2 1/2と同じ)										
13mmMG	0.7~13	0.3	K-2	6.5	44.5	80	63.5	19	500	JT2S,JT1	SUS13		
13MGネジ	0.7~13											1/2-20UNF	
			5/8-16UNF	K-13	8	55	88.5	68.5	26	700	JT33,B16 JT2S,JT1	SUS13ネジ	
14mm	0.7~14		JT3	K-14	9	59.5	96	73.5	26	915	JT6,JT2SS JT33		
16mm	3.2~16												
19mm	0.8~19		JT4	K-4	9.5	74	126	96.5	31.5	1830	JT3,JT6 JT33		
22mm	5~22												
25mm	6~25.4		JT5	K-5	10.9	88	149	110.5	44	2880	JT4,JT6		