

| | | | | | | | | | | | 特殊仕様 | |
|---------|------------|---------|------------|------------|------------|------|----------------|----------------|-------|--------------|-------------------|---------|
| 型式 | 標準 使用範囲 | 小径用使用範囲 | 標準取付け形式 | 適合 ハンドル | ハンドル 穴径 | D | L ₁ | L ₂ | ツメリード | 重量 (g) 本体 | 標準以外のテーパ | ステンレス製 |
| 3mm | 0.4~3.2 | 0.1、0.2 | JT0 | K-03 | 3.2 | 21 | 34 | 28.5 | 10 | 44 | | SUS4 |
| 4mm | 0.4~4 | 0.1、0.2 | | | | | | | | | | |
| D4mm | 0.4~4 | 0.1、0.2 | JTD | K-00 | 4 | 25 | 40 | 32.5 | 11 | 78 | | |
| D5mm | 0.4~5 | 0.1、0.2 | | | | | | | | 73 | | |
| 5mmMG | 0.5~5 | 0.2 | JT1 | K-01 | 4 | 31 | 48.5 | 40.5 | 12 | 138 | JT0 | SUS6.5 |
| 6.5mmEL | 0.5~6.5 | | | | | | | | | 136 | | |
| 6.5ELネジ | 0.5~6.5 | | ⅜-24UNF | K-1A | 5.5 | 35.5 | 54 | 45 | 13 | 200 | JT0 | SUSJ8 |
| 6.5mmMG | 0.5~6.5 | | JT1 | | | | | | | 200 | | |
| J8mm | 0.5~8 | | ⅜-24UNF | K-1A | 5.5 | 35.5 | 65 | 55 | 13 | 300 | JT1,JTD | SUS10 |
| J8mmネジ | 0.5~8 | | ⅜-24UNF | | | | | | | | | |
| 10mmEL | 0.5~10 | | JT2S | K-2 | 6.5 | 44.5 | 80 | 63.5 | 19 | 500 | JT2S,JT1 | |
| 10mmMG | 0.5~10 | 0.3 | (角度は2と同じ) | | | | | | | | | |
| 10MGネジ | 0.5~10 | | ½-20UNF | K-13 | 8 | 55 | 88.5 | 68.5 | 26 | 700 | JT33, JT2S,JT1 | SUS13 |
| 13mmEL | 0.7~13 | | JT6 | | | | | | | | | |
| 13mmMG | 0.7~13 | 0.3 | (JT2 ½と同じ) | K-13 | 8 | 55 | 88.5 | 68.5 | 26 | 700 | JT33, JT2S,JT1 | SUS13 |
| 13MGネジ | 0.7~13 | | 1/2-20UNF | | | | | | | | | |
| | | | 5/8-16UNF | | | | | | | | | SUS13ネジ |
| 14mm | 0.7~14 | | JT3 | K-14 | 9 | 59.5 | 96 | 73.5 | 26 | 915 | JT6,JT2SS | |
| 16mm | 3.2~16 | | | | | | | | 31 | 910 | | |
| 19mm | 0.8~19 | | JT4 | K-4 | 9.5 | 74 | 126 | 96.5 | 31.5 | 1830 | JT3,JT6 | |
| 22mm | 5~22 | | | | | | | | 36 | 1800 | | |
| 25mm | 6~25.4 | | JT5 | K-5 | 10.9 | 88 | 149 | 110.5 | 44 | 2880 | JT4,JT6 | |